

Coefficients Of Utilization - Zonal Cavity Method

Effective Floor Cavity Reflectance: 20%

RCC %:	80				70				50			30			10			0
RW %:	70	50	30	0	70	50	30	0	50	30	20	50	30	20	50	30	20	0
RCR: 0	1.00	1.00	1.00	1.00	.98	.98	.98	.84	.93	.93	.93	.89	.89	.89	.86	.86	.86	.84
1	.91	.87	.83	.80	.89	.85	.81	.70	.81	.78	.76	.78	.76	.74	.75	.73	.71	.70
2	.82	.75	.69	.64	.80	.73	.68	.58	.70	.65	.61	.67	.63	.60	.65	.62	.59	.57
3	.74	.65	.58	.52	.72	.64	.57	.48	.61	.55	.51	.59	.54	.50	.57	.52	.49	.47
4	.68	.57	.49	.43	.66	.56	.49	.41	.54	.48	.43	.52	.46	.42	.50	.45	.41	.39
5	.62	.51	.43	.37	.60	.50	.42	.35	.48	.41	.36	.46	.40	.36	.45	.40	.35	.34
6	.57	.45	.38	.32	.55	.45	.37	.31	.43	.36	.31	.42	.36	.31	.40	.35	.31	.29
7	.53	.41	.33	.28	.51	.40	.33	.27	.39	.32	.28	.38	.32	.27	.36	.31	.27	.25
8	.49	.37	.30	.25	.48	.37	.30	.24	.35	.29	.24	.34	.29	.24	.33	.28	.24	.22
9	.46	.34	.27	.22	.44	.33	.27	.22	.33	.26	.22	.32	.26	.22	.31	.25	.22	.20
10	.43	.31	.24	.20	.42	.31	.24	.19	.30	.24	.20	.29	.24	.20	.28	.23	.20	.18

Visual Photometric Tool 1.2.19 copyright 2009, Acuity Brands Lighting  
 Reported data calculated from manufacturer's data file, based on IESNA recommended methods.